

Product Data Sheet



STARFIX AX 131

One Component, High Performance, Multi Use, Anti-Fungal & Anti-Bacterial Acetoxy Silicone Sealant

Uses:

- Sanitary Installations (Bathtubs, Washbasins, Kitchen)
- Aluminum, Window and Door Installation
- General elastic Adhesive for various materials (Glass, Wood, Metal, Ceramics, PVC)
- Non- structural Glazing

Product Description

STARFIX AX 131 is a single component, Acetic cured, high elastomeric joint sealant - An excellent all-purpose silicone sealant formulated to provide a fast-setting pliable seal with minimal shrinkage.

The product is designed as a general-purpose sealant to seal cracks and joints and is recommended for sealing interior joints between walls and panels, around door frames and base boards and also joints between bathroom features and walls. This product has powerful anti-fungicide property to prevent mould/bacteria growth.

Advantages

- Good working and smoothing properties
- Cures at ambience – Depends on temperature and humidity.
- Anti-Fungal & Anti-Bacterial
- Acetic odor, free of solvents
- Good UV-resistance – No color fading
- Non -Sagging (Thixotropic)
- Fast dry
- Excellent Adhesion and bonding on multiple substrates.

Standard Compliance

- ASTM C679
- ASTM C639
- ASTM D1475

Technical Properties

STARFIX AX 131	Typical Values @ Laboratory Conditions
Physical Appearance	Thixotropic Smooth Paste
Available Colors	Standard Colors, White, Black Clear. Grey, Other colors based on request.
Specific Gravity, kg/l (ASTM D 1475)	Approx 0.96
Tack free time, min. (ASTM C679)	Approx 10
Skin Over time, min. (ASTM C679)	Approx 5
Depth Cure, mm @ 24 hrs @ +23°C/50% RH	≥ 2.5
Hardness Shore A (ASTM D 2240-15)	Approx 24
Tensile Strength, MPa (ASTM D 412-16)	Approx. 1.00
Elongation % (ASTM D 412-16)	≥ 250
Modulus at Elasticity, MPa (ASTM D 1784-20)	≥ 0.4
Service Temperature, °C	- 5 to + 130
Application Temperature, °C	5 to 35

Product Data Sheet

Application

Surface Preparation

The surface should be clean, dry, sound and free from oil, grease and wax contamination. Cement laitance, loose particles, mold release agent or curing membranes must be removed.

Before positioning a bond breaker, check the expansion joint filler to ensure it is tightly packed with no gaps or voids at the base of the sealing slot.

To avoid adhesion on 3 flanks or in the event of deeper joints use Backing Rods.

Priming

Priming is normally not required on good quality substrates.

Application

STARFIX AX 131 JOINT SEALANT application should follow standard concrete joints practices; Sealants need either backing rod or joint breaker tapes to prohibit 3-point adhesion and allow movement freedom. STAR Technology refers to ACI 224.3-95 for joint design.

Standard Joint Design:

Joint Distance (m)	2	2 – 3.5	3.5 – 5	5 – 6.5	6.5 - 8
Joint Width	15	20	25	30	35
Min Joint Width	10	15	20	25	30
Joint Depth	8	10	12	15	15

Joint Size Suitability:

Joint Width	6mm to 20mm – Single Application
Joint Depth	Maximum 10mm on porous substrate and max 6mm on non-porous substrate
Width : Depth	1 : 1

Apply **STARFIX AX 131** and smoothen it within 10 min. after application.

Pull off the masking tape in the direction of the joint before skin forms.

Curing and protection

STARFIX AX 131 forms a Skin within approx. 5 min after application and cures at a rate of approx. 3mm per 24hrs – Tack Free condition should be reached after approx. 10-15 mins.

Cleaning:

Remove **STARFIX AX 131** from product from tools, equipment, and mixers with STAR Solvent before the initial set. Cured material can only be removed mechanically.

Packing & Coverage

STARFIX AX 131 is packed in Standard Cartridges

Joint Size in mm	Yield in m per “Cartridge”
6 x 6	5
9 x 6	4
12 x 6	2
15 x 10	1.5

Shelf Life & Storage

The original sealed Box **STARFIX AX 131** has a shelf life of 12 months, provided it is stored in a dry shaded place below 86°F (30°C).at standards warehouse conditions. Containers should always be kept sealed when not in use.

Health & Safety

As with all chemicals, caution should always be exercised. Protective clothing such as gloves and goggles should be worn.

STARFIX AX 131 is not considered hazardous – But contains Silicones.

For detailed information and advice on the safe handling, storage, and disposal of chemical products, users shall refer to the most recent Material Safety Data Sheet containing physical, ecological, toxicological, and other safety-related data.

For complete Health and Safety instructions and information, please refer to STAR MSDS.

K E EP OUT OF REA CH OF CHILDR EN • K E EP CONTAINER TIG HTLY CLOSE D • FOR INDUSTRIAL & PROFESSIONAL USE

Product Data Sheet

Additional Information:

STAR manufactures a wide range of construction chemicals and specialty products for various applications divided into the following product sections:

1. **Waterproofing Products**
2. **Sealants, Grouts, and Joint Fillers**
3. **Adhesives**
4. **HVAC – Adhesives, Coatings & Sealants**
5. **Flooring Products**
6. **Industrial Adhesives (i.e. Paper Industry)**
7. **Accessories**

STAR Technology provides various technical information such as detailed method statements, specification clauses, application manuals and technical support both in contractors and consultant's offices as well as construction sites.

For further information on these products and systems kindly visit our website or contact your local STAR representative